

The following features are available in this PDF document.



Quick Keyword Search

Enter the keyword in the search box and hit the search button



Quick Jump between Chapters

Click the title of a specific chapter on the Contents to jump to it

*Reading software such as Adobe Reader is needed to support the functions above.



ZHIYUN CINEPEER WEEBILL 3E

User Guide


Contents

□ Product List	
Product List	1
□ Get to Know ZHIYUN CINEPEER WEEBILL 3E	
Get to Know ZHIYUN CINEPEER WEEBILL 3E	3
□ Battery and Charging	
Battery and Charging	6
□ Mounting and Balancing	
Mounting the Tripod	7
Mounting the Camera	7
Balancing	13
□ How to Use ZHIYUN CINEPEER WEEBILL 3E	
Button Description	15
Display Screen Description	16
Icon Description	17
Menu Description	19
Motor Torque Adjustment	23
Bluetooth Shutter Control	25
Gimbal Mode Description	26
Manual Reposition	29
□ How to Use the App	
Downloading the App	30
How to Connect	30
ZY Play Feature Description	32

□ Firmware Upgrade & Calibration	
Circumstances When Calibration Is Needed	33
Six-side Calibration	33
Motor Fine-Tuning	35
Firmware Upgrade	35
□ Product Specifications	
□ Disclaimer and Warning	
Reading Tips	42
WARNING	42
Safe Operation Guidelines	43
□ Warranty Card	
Warranty Period	44
Warranty Exclusions	44
Warranty Claim Procedure	44
□ Contact Card	

Product List


Before using this product, please check carefully that all the following items are included in the product package. In case that any item is found missing, please contact ZHIYUN or your local selling agent.



WEEBILL 3E (Standard) x1*




WEEBILL 3E (Lite) x1*




Quick Release Plate x1



Tripod x1**



USB Type-C Cable x1

Type-C to Type-C USB LN-UCUC-A02
Camera Control Cable x1



Quick Start Guide x1




1/4" Screw x1
M4 Wrench x1

Purchasing ZHIYUN CINEPEER WEEBILL 3E Standard version or Lite version includes the corresponding version of the gimbal.


“***” are included in WEEBILL 3E standard version.

Get to Know ZHIYUN CINEPEER WEEBILL 3E

Standard Version



- | | |
|--|---------------------------|
| 1. Quick Release Plate Leveling Base | 10. 1/4" Threaded Hole |
| 2. Leveling Base Safety Lock | 11. Tilt Axis Motor |
| 3. Quick Release Plate Latch | 12. Camera Control Port |
| 4. Quick Release Plate Leveling Base Latch | 13. Roll Axis Motor |
| 5. Pan Axis Lock Switch | 14. Roll Axis Lock Switch |
| 6. Pan Axis Motor | 15. Display Screen |
| 7. Joystick | 16. Mode Switch |
| 8. Photo/Video Button | 17. Gimbal Handle |
| 9. Firmware Upgrade/Charging Port | 18. Tripod |



19. Tilt Axis Lock Switch

20. Pan Axis Latch

21. Power Button

22. Menu/Return Button

23. Control Wheel

24. Leveling Base Lock Screw

25. Quick Release Plate Safety Lock

26. Quick Release Plate


27. Level Mount

28. Level Mount Lock Screw

29. Trigger Button

30. Adjustment Wheel

Lite Version



- 1. Quick Release Plate
- 2. Quick Release Plate Leveling Base
- 3. Quick Release Plate Latch
- 4. Level Mount


- 5. Quick Release Plate Safety Lock
- 6. Quick Release Plate Leveling Base Latch

💡 Unlisted components of the Lite version gimbal are the same as those of the Standard version.

Battery and Charging

ZHIYUN CINEPEER WEEBILL 3E adopts built-in battery. When using ZHIYUN CINEPEER WEEBILL 3E for the first time, please activate the gimbal by fully charging the battery to ensure the proper function of the gimbal.


Charging method: Use provided USB Type-C cable to connect the USB charger (not included in the package) to charge ZHIYUN CINEPEER WEEBILL 3E. It is recommended to use USB chargers that meet the PD protocol. (supports 14W PD charging at most).



- ① USB charger is not provided.
- ② Please power off ZHIYUN CINEPEER WEEBILL 3E to charge.


Mounting the Tripod

Mount the tripod to the bottom of the ZHIYUN CINEPEER WEEBILL 3E handle, then unfold the tripod and place the ZHIYUN CINEPEER WEEBILL 3E on a flat surface.



Mounting the Camera

1. Each axis of the gimbal is equipped with a lock switch. You can use these lock switches to lock the axes for convenient installation and storage. The storage state is the default state. Please toggle the lock switch to unlock the three axes, expand the gimbal as shown in the image, and lock the axes again for convenient camera installation.




Locked state for storage

Locked state for installation

- ① Please mount the camera before powering on ZHIYUN CINEPEER WEEBILL 3E and balance the gimbal. Do not power on ZHIYUN CINEPEER WEEBILL 3E when there's no camera mounted on it.
- ② Before mounting the camera, make sure it is prepared ahead of time. Remove the lens cap and make sure the camera's battery and memory card are already in place.


2. Mount the camera on the quick release plate ①, and tighten the screw ②.



Installation Steps for Standard Version


(1) Installation for Landscape Orientation

Unlock the quick release plate latch ①, install the quick release plate and camera onto the quick release plate leveling base ② and then tighten the latch ③.




(2) Installation for Portrait Orientation

Unlock the quick release plate leveling base latch ① . Press and hold the leveling base safety lock ② and push the leveling base to the left until it is removed from the level mount ③ . Install the camera and quick release plate as a whole onto the leveling base ④ and tighten the latch ⑤ . Install the camera, quick release plate, and leveling base as a whole onto the level mount ⑥ . Tighten the leveling base lock screw ⑦ .



- 💡 When disassembling at horizontal orientation, please unlock the quick release plate latch ① and hold down the safety lock of the quick release plate ② to remove the camera and quick release plate as a whole ③ .




- 💡 When disassembling at portrait orientation, please loosen the screw that locks the leveling base ① , and hold down the safety lock of the leveling base ② to remove the camera, quick release plate and leveling base as a whole from level mount ③ .




Installation Steps for Lite Version

Install the quick release plate and camera onto the quick release plate leveling base ① and then tighten the quick release plate latch ②.



⚠ When disassembling, please unlock the quick release plate latch ① and hold down the safety lock of the quick release plate ② to remove the camera and quick release plate as a whole ③.




- (2) Connect the camera control cable to the camera control port of the gimbal and the camera.




Balancing

1. Horizontal Balance of the Tilt Axis

Unlock the tilt axis lock switch ① and loosen the quick release plate latch ② . Push the camera to move forward or backward ③ until the camera can stay still and almost level with its lens facing front ④ . Complete this step by tightening up the quick release plate latch ⑤ .


**2. Vertical Balance of the Tilt Axis**

Make the lens face up, loosen the level mount lock screw ① . Push the whole level mount to move forward or backward ② . Push until the camera can stay still with the lens facing up (i.e.the camera stays still and vertical to the ground) ③ . Complete this step by tightening up the screw ④ .




3. Roll Axis Balance

Unlock the roll axis ① and loosen the quick release plate leveling base latch ②. Push the camera to move left or right ③ until the camera can stay still and horizontal to the ground ④. Complete this step by tightening up the latch ⑤.





4. Pan Axis Balance

Unlock the pan axis ①, loosen the pan axis latch ②, hold and slightly tilt the handle, push the pan axis to move left or right ③ until the pan axis can stay still in any position. Complete this step by tightening up the pan axis latch ④.



- 💡 ① The balancing steps for the portrait orientation are the same as the landscape orientation.
- ② The balancing method of ZHIYUN CINEPEER WEEBILL 3E Lite is the same as the Standard version.
- ③ After balancing ZHIYUN CINEPEER WEEBILL 3E, the motor torque needs to be adjusted for proper function. For the adjustment details, please see the methods introduced in "Motor Torque Adjustment".

Button Description



1. Joystick

Push up/down/left/right to control the gimbal to rotate.



2. Photo/Video Button

Half press: Activate auto-focus on certain cameras.

Long press: Take a photo.

Single press: Start/stop filming a video.



3. Mode Switch

Single press: Switch among PF/L/F mode.

Double press: Switch among POV/V/Portrait mode.

Long press: Sleep/wake mode for the gimbal motors.



4. Power Button

Long press: Turn on/off the gimbal.



5. Menu/Return Button

Single press: Enter/exit main menu. When in the submenu, press to return to the previous menu.



6. Control Wheel

Single press: Confirm

Scroll: Select menu/adjust parameter



7.Trigger Button

Single press: Switch to customized gimbal mode (Follow mode by default)/Return to the previous mode.

Double press: Gimbal reposition.

Triple press: Selfie mode.

Long press: Enter Go mode. Release to return to the previous mode. When in the portrait orientation, long press to lock the gimbal. Motors of three axes won't move with the handle. Release to unlock the gimbal and the motors of tilt axis and roll axis will move with the handle.



8. Adjustment Wheel

Scroll: Adjust parameters customized in the screen menu (aperture, shutter, ISO, digital focus/zoom, roll axis, tilt axis, pan axis).

Display Screen Description




Main page
(set as default)




Main interface
(when connected to camera)



Shooting a video



Main menu



Axis locked



Standby

Icon Description

	Camera and gimbal are successfully connected
	Current gimbal battery level
 axis lock	Indicates that the locks on the three axes have not been released and an alarm will sound (press and hold the M button to release the locks, and resume operation).
	Standby icon, displayed when the motor is in sleep mode
	Camera connected to gimbal
	Camera shooting a video
	Gimbal connected to camera Bluetooth
PF	Gimbal in Pan Follow Mode
L	Gimbal in Lock Mode
POV	Gimbal in Point Of View Mode
V	Gimbal in Vortex Mode
F	Gimbal in Follow Mode
GO	Gimbal in Go Mode
P	Gimbal in Portrait Mode

AV	Current camera aperture value
TV	Current camera shutter speed
ISO	Current camera ISO value
	Current camera EV value

Menu Description

Motor Torque	Auto Calibration		
	Custom	Tilt axis	
		Roll axis	
		Pan axis	
	Level	Low	
		Medium	
High			
Parameter Settings	Speed	Joystick control	Tilt axis
			Roll axis
			Pan axis
		Motor follow speed	Tilt axis
			Roll axis
			Pan axis
	Smoothness	Tilt axis	
		Roll axis	
		Pan axis	
	Deadband	Tilt axis	
		Roll axis	
		Pan axis	

Parameter Settings	Restore Default Settings	Confirm
		Cancel
Bluetooth Shutter Control	Please check if you turn on the camera Bluetooth...	
Control Wheel Setting		Electronic follow focus
		Electronic zoom
		Aperture
		Shutter
		ISO
		Tilt axis
		Roll axis
		Pan axis
	Disable control wheel	
Control Wheel Setting	Reverse	Off
		On
	Sensitivity	Low
		Medium
		High

Joystick Setting	Reverse	Vertical	Off
			On
	Horizontal		Off
			On
Trigger Button Function	PF/L/F/POV/V/P	Set the operation mode when pressing the trigger button once	
V Mode Settings*	Speed	Rotation speed	
	Orientation	Clockwise	
		Counterclockwise	
	Angle	Unlimited	
		Custom	Turns
Start			
Motionlapse	Preset	Two preset paths available: preset1/preset 2	
	Mode	Two modes available: photo/video	
	Points	Five at most key points can be set (A, B, C, D, E)	
	Time	"interval" for the time interval of photo taking, "duration" for the total amount of time	
	Preview	Quick preview of the set path	
	Start	Enable motionlapse	

Angle Finetuning	Tilt axis
	Roll axis
Restore Default Settings	Confirm
	Cancel
Language	Simplified Chinese
	English
About	Product Name, Firmware Version, Bluetooth Name

*To enter: Switch the gimbal mode to V mode, press the control wheel in the V Mode Setting menu.

To exit: Single press the mode switch.

Motor Torque Adjustment

After balancing ZHIYUN CINEPEER WEEBILL 3E, the motor torque needs to be adjusted for proper function. You can adjust the motor torque according to the weight of your camera and lens, so that the ZHIYUN CINEPEER WEEBILL 3E can be used in its ideal state. Following are three methods for adjustment. It is recommended to use auto-calibration.

1. Auto Calibration

Auto calibration will adjust the motor torque according to the weight of the carried camera and lens.

Operation steps: Press Menu / Return button to enter the menu. Select "Motor Torque" and enter the next menu. Select "auto calibration" and press the control wheel to confirm. The gimbal will then enter auto calibration mode. Please don't touch the gimbal and wait for the display screen to show the "√" mark after the gimbal shakes. The auto calibration is then complete.

2. Custom

The power determines the torque of the motor, and needs to be adjusted according to the camera and the lens on the gimbal. The power should be proportional to the weight of the load. A high power value will cause the gimbal itself to vibrate, while a value that is too low will affect the stability of the gimbal.

Operation steps: Press Menu/Return button to enter the menu and select "Motor Torque". Press the control wheel to enter the next menu. Scroll the control wheel to select "custom" and press the control wheel to enter the adjustment interface. Scroll the control wheel to select the axis you wish to adjust and press the control wheel to confirm. To set the power value, you can scroll the control wheel. To complete the setting, press the control wheel to exit the interface, press the Menu/Return button to save the settings and return to the previous menu. When the display screen shows the "√" mark, the adjustment is complete.

3. Level

Three motor torque levels from low to high are provided based on the combined weight of mainstream camera lenses available on the market. Users can select the corresponding motor torque level according to the weight of their camera and lens.

Operation steps: Press Menu/Return button, select "Motor Torque" and press the control wheel to enter the next menu. Scroll the control wheel to select "Level" and press the control wheel for the next menu. Select your desired level and press the control wheel to confirm. When the display screen shows the "√" mark, the selection is complete.

- ① When adjusting the motor torque, make sure that the lock switches of the three axes on the gimbal are turned on, and the gimbal is upright and placed on level ground.
- ② If a load is changed, please readjust the balance and adjust the power values using the method mentioned above.
- ③ It is recommended to use auto-calibration first. If auto-calibration fails to meet your requirements, you can use custom settings to fine-tune the values. If the above two methods still do not meet your requirements, use the level adjustment to select the power.

Bluetooth Shutter Control

ZHIYUN CINEPEER WEEBILL 3E supports Bluetooth shutter control, which allows you to wirelessly control the camera shutter without connecting a camera control cable. Before connecting the camera Bluetooth to ZHIYUN CINEPEER WEEBILL 3E, please turn on the camera's Bluetooth and enter pairing mode. Then press the menu/return button on ZHIYUN CINEPEER WEEBILL 3E to enter the main menu, scroll the control wheel and select Bluetooth shutter control, and single press the control wheel to confirm. ZHIYUN CINEPEER WEEBILL 3E will then automatically search for the camera Bluetooth name. Select the Bluetooth name that needs to be connected, press the control wheel to confirm the connection, and finally confirm the connection on the camera.


- ① After ZHIYUN CINEPEER WEEBILL 3E and the camera complete pairing and successfully connect Bluetooth for the first time, they can automatically connect to Bluetooth next time.
- ② When ZHIYUN CINEPEER WEEBILL 3E and the camera are connected through both camera control cables and Bluetooth at the same time, the gimbal prioritizes controlling the camera function through the camera control cable.
- ③ After ZHIYUN CINEPEER WEEBILL 3E and the camera are connected via Bluetooth, the Bluetooth connection can be disconnected in the Bluetooth shutter control menu.
- ④ For specific camera models that support Bluetooth control in ZHIYUN CINEPEER WEEBILL 3E please visit the ZHIYUN official website www.zhiyun-tech.com to check the "ZHIYUN CINEPEER WEEBILL 3E Camera Compatibility List" for the latest information.

Gimbal Mode Description

💡 Motors circled in red are free to move in line with the movement of the gimbal handle while motors circled in grey are locked.


Pan Follow mode (PF):

The tilt axis and roll axis motors are locked, and the camera rotates with the handle while panning horizontally. Push the joystick up / down to control the tilt axis angle, and push it left/right to control the pan axis of the camera.




Lock mode (L):

All three motor angles are locked, and the camera orientation will not move with the rotation of the handle. Push the joystick up / down to change the tilt angle of the camera and left / right to change the horizontal orientation of the camera.




Follow mode (F):

The roll axis motor is locked, and the tilt axis and pan axis motors follow the rotation of the handle. Push the joystick up/down to change the tilt angle of the camera and left/right to change the horizontal orientation of the camera.


**Point of View mode (POV):**

All three motors move when the handle is rotated. Push the joystick up/down to change the tilt angle of the camera and left/right to change the horizontal orientation of the camera.




Vortex mode (V):

The tilt axis motor rotates upward by 90°, and the tilt axis, roll axis, and pan axis motors follow the rotation of the handle. Push the joystick to the left/right to control the rotation of the pan axis.




Go mode (GO):

The roll axis motor is locked, and the tilt axis and pan axis motors quickly follow the rotation of the handle. Push the joystick up/down to change the tilt angle of the camera and left/right to change the horizontal orientation of the camera.




Portrait mode (P):

The tilt axis motor rotates upward by 90° and the pan axis rotates counterclockwise by 90° . You can enter this mode for vertical shooting.



Manual Reposition

In Pan Follow mode (PF), Lock mode (L), and Follow mode (F), the camera can be rotated by a certain angle by hand. Hold it for 2s and the camera angle will be fixed at that angle after you release the camera (tilt axis, pan axis).



Downloading the App







Scan the QR code on the left (Android 5.0 and above, iOS 9.0 and above required) or search "ZY Play" in App Store or Google Play to download.

- ① "ZY Play" is an app dedicatedly designed for ZHIYUN CINEPEER WEEBILL 3E. When activated ZHIYUN CINEPEER WEEBILL 3E via "ZY Play", you can also use it for firmware upgrades, virtual joystick control, six-side calibration, etc.
- ② ZY Play is subject to updates without notice. Please always refer to the latest version.

How to Connect

1. Power on ZHIYUN CINEPEER WEEBILL 3E and turn on Bluetooth on the smartphone.
2. Launch the "ZY Play" app. Select the ZHIYUN CINEPEER WEEBILL 3E page and tap to connect. Select the Bluetooth name of your ZHIYUN CINEPEER WEEBILL 3E to connect (the WEEBILL 3E Bluetooth name can be found on the side of the tilt axis USER ID: XXXX).
3. If the ZHIYUN CINEPEER WEEBILL 3E is being used for the first time, you need to activate the gimbal via "ZY Play" to use the advanced features in the app. Internet connection is required.
4. After the activation succeeds, you can enter the feature interface of ZY Play App.



ZY Play Feature Description



💡 For more details of the “ZY Play” app features, please visit the official website of ZHIYUN (www.zhiyun-tech.com) and watch ZHIYUN CINEPEER WEEBILL 3E video tutorials.

Circumstances When Calibration Is Needed

Calibrate the gimbal as needed.

Calibration Reason	Calibration Method
1. Slight deviation is found in the level position after the initialization of the gimbal. 2. The gimbal has not been used for a long time. 3. The gimbal undergoes significant temperature differences in operation environments.	Six-side Calibration
Slight deviation is found in the tilt or roll angle in level position after six-side calibration of the gimbal.	Motor finetuning

Six-side Calibration

1. Six-side calibration via APP:


According to the method introduced in "How to Use the App", please connect the gimbal to the APP, and enter "Settings" - "Six-side Calibration", then conduct the six-side calibration according to the prompt.

2. Six-side calibration via "Zhiyun Gimbal Tools":


Power on the gimbal and enter standby mode. Connect the charging/upgrade port of the gimbal to the computer with the Type-C USB cable, Open "Zhiyun Gimbal Tools", click "open" on the top and click "calibration" on the bottom. Please conduct the process according to the following steps. A "√" mark will appear after the calibration is completed.

- 💡 ① Please refer to the six-side calibration steps below. After the calibration is completed, please restart the gimbal.
- ② In simple terms, six-side calibration is to place all six sides of the quick release plate vertically to a level surface respectively.


Step 1




Step 2




Step 3




Step 4



Step 5



Step 6



Motor Fine-Tuning


Select “Motor Fine-tuning” in the main menu to fine-tune the value of the tilt axis and roll axis according to actual needs.




Firmware Upgrade

You can use “Zhiyun Gimbal Tools” or “ZY Play” app to perform ZHIYUN CINEPEER WEEBILL 3E firmware upgrade.

Method One:

1. Visit the official website of ZHIYUN (www.zhiyun-tech.com), go to the ZHIYUN CINEPEER WEEBILL 3E product page, click “Download”, find the USB driver, the calibration upgrade tool and the firmware and download. (USB drivers are not required for Mac OS systems)
2. Install the driver, unzip the firmware for the documents with the “.ptz” file extension.
3. Connect the Type-C charging/upgrade port of ZHIYUN CINEPEER WEEBILL 3E to the computer with the Type-C USB cable, power on ZHIYUN CINEPEER WEEBILL 3E.
4. Open “Zhiyun Gimbal Tools”, click “Open”, click “Firmware Upgrade”. Click “Browse” under “Path” to select the latest firmware downloaded (with the “.ptz” file extension), and click “Upgrade” at the bottom to upgrade firmware.





Method Two:

When ZHIYUN CINEPEER WEEBILL 3E is connected to “ZY Play” app, if a firmware update prompt pops up on the app, please follow the instructions to upgrade. Internet connection is required. To know how you can connect ZHIYUN CINEPEER WEEBILL 3E to “ZY Play”, please check the method introduced in “How to Use the App”.

- ① When upgrading with Method 1, please wait until the screen displays that the upgrade is finished, then you can plug out the USB Type-C cable.
- ② Before upgrading the firmware, please ensure that the ZHIYUN CINEPEER WEEBILL 3E has more than 50% power remaining. You cannot exit the app interface or access in the background during the upgrading process. Pay attention to the prompts on the app.

Product Model: CR129 (Lite)

Item	Min.	Standard	Max.	Remark
Operation Voltage	6.5V	7.4V	8.4V	
Operation Current	150mA	-	5300mA	
Output Voltage (Camera Control Port)	-	5V	-	
Output Current(Camera Control Port)	-	1A	-	
Tilt Mechanical Range	-130°	-	+180°	
Roll Mechanical Range	-280°	-	+60°	
Pan Mechanical Range	-	360°	-	Unlimited Rotation
Controllable Tilt Angle	-90°	-	+160°	
Controllable Roll Angle	-30°	-	+35°	
Controllable Pan Angle	-	360°	-	
Operation Temperature	-10°C	25°C	45°C	
Battery Capacity	-	2600mAh	-	2 18650 lithium batteries
Battery Runtime		16H		Lab Data 1
Charging Time		2H		Lab Data 2
Gimbal Net Weight		990g		

Item	Min.	Standard	Max.	Remark
Quick Release Plate Weight		70g		
Gimbal Size (Folded)		305*210*72.5mm		
Gimbal Size (Expanded)		306.3*158*177.3mm		Without tripod
Bluetooth		Bluetooth 5.0		
EIRP		<10dBm		
Operation Frequency		2.4 GHz		
Camera Charging		Able to charge 5V / 1A cameras		
1/4" Rosette Mount Screw Thread Carry Weight		≤ 3000g		

Product Model: CR130 (Standard)

Item	Min.	Standard	Max.	Remark
Operation Voltage	6.5V	7.4V	8.4V	
Operation Current	150mA	-	5300mA	
Output Voltage (Camera Control Port)	-	5V	-	
Output Current(Camera Control Port)	-	1A	-	
Tilt Mechanical Range	-130°	-	+180°	
Roll Mechanical Range	-280°	-	+60°	
Pan Mechanical Range	-	360°	-	Unlimited Rotation
Controllable Tilt Angle	-90°	-	+160°	
Controllable Roll Angle	-30°	-	+35°	
Controllable Pan Angle	-	360°	-	
Operation Temperature	-10°C	25°C	45°C	
Battery Capacity	-	2600mAh	-	
Battery Runtime		16H		Lab Data 3
Charging Time		2H		Lab Data 4
Gimbal Net Weight		1.05kg		

Item	Min.	Standard	Max.	Remark
Quick Release Plate Weight		70g		
Tripod Weight		50g		
Gimbal Size (Folded)		305*210*72.5mm		
Gimbal Size (Expanded)		306.3*158*177.3mm		Without tripod
Bluetooth		Bluetooth 5.0		
EIRP		<10dBm		
Operation Frequency		2.4 GHz		
Camera Charging		Able to charge 5V / 1A cameras		
1/4" Rosette Mount Screw Thread Carry Weight		≤ 3000g		

Lab Data 1: The above data is collected at a specified temperature of 25°C. The ZHIYUN CINEPEER WEEBILL 3E Lite is fully charged with 18650-2600mAh batteries and mounted with Sony A7M4+FE 24-70mm F4 ZA OSS. The ZHIYUN CINEPEER WEEBILL 3E is properly balanced and put on a flat surface. The maximum runtime is 16H. When the battery powers the gimbal, it also charges the camera simultaneously. The battery life will be shortened in this case, so you should determine whether to turn on the camera USB power supply function. The actual duration of use will vary depending on the length of time the ZHIYUN CINEPEER WEEBILL 3E is used, the number of times the battery is charged and discharged, as well as the battery's vitality. The longer the ZHIYUN CINEPEER WEEBILL 3E is used, the more times the battery is charged and discharged, and the lower the battery vitality, the shorter the duration of use..

Lab Data 2: The data is collected when charging with a 14W PD Fast Charging at a specified temperature of 25°C. The charging time is 2h. The actual charging time varies with environmental factors. In addition, the lower the temperature, the longer the charging time.

Lab Data 3: The above data is collected at a specified temperature of 25°C. The ZHIYUN CINEPEER WEEBILL 3E is fully charged with 18650-2600mAh batteries and mounted with Sony A7M4+FE 24–70mm F4 ZA OSS. The ZHIYUN CINEPEER WEEBILL 3E is properly balanced and put on a flat surface. The maximum runtime is 16H. When the battery powers the gimbal, it also charges the camera simultaneously. The battery life will be shortened in this case, so you should determine whether to turn on the camera USB power supply function. The actual duration of use will vary depending on the length of time the ZHIYUN CINEPEER WEEBILL 3E is used, the number of times the battery is charged and discharged, as well as the battery's vitality. The longer the ZHIYUN CINEPEER WEEBILL 3E is used, the more times the battery is charged and discharged, and the lower the battery vitality, the shorter the duration of use..

Lab Data 4: The data is collected when charging with a 14W PD Fast Charging at a specified temperature of 25°C. The charging time is 2h. The actual charging time varies with environmental factors. In addition, the lower the temperature, the longer the charging time.

All the data is collected from internal experiments of ZHIYUN laboratories. Under different scenarios, the above data is subject to a margin of error. Please refer to actual use of this product.

Thank you for purchasing this product. The information contains herein affects your safety, legitimate rights and obligation. Please read this instruction carefully to ensure proper configuration before use. Failure to read and follow this instruction and warnings herein may result in serious injury to you or bystanders, or damage to your device or property. Guilin Zhishen Information Technology Co., Ltd (hereinafter referred to as "ZHIYUN") reserves all rights for final explanation on this instruction and other documents related to the product. The information is subject to update without notice. Please visit www.zhiyun-tech.com to obtain the latest product information.

By using this product, you hereby signify that you have read this document carefully and that you understand and agree to abide by the terms and conditions herein. You agree that you are solely responsible for your own conduct while using this product, and for any consequences thereof. You agree to use this product only for purposes that are proper and in accordance with all terms, precautions, practices, policies and guidelines ZHIYUN has made and may make available.

ZHIYUN accepts no liability for damage, injury or any legal responsibility incurred directly or indirectly from the use of this product. Users shall observe safe and lawful practices including, but not limited to, those set forth herein.

ZHIYUN™ are the trademark of Guilin Zhishen Information Technology Co., Ltd and its affiliates. All product names or trademarks referred to herein are trademarks or registered trademarks of their respective holders.

Reading Tips

Legends:  Hints and Tips

 Important

WARNING

Read the ENTIRE User Guide to become familiar with the features of this product before operating. Failure to operate the product correctly can result in damage to the product or personal property and cause serious injury. This is a sophisticated product. It must be operated with caution and common sense and requires some basic mechanical ability. Failure to operate this product in a safe and responsible manner could result in injury or damage to the product or other property. This product is not intended for use by children without direct adult supervision. DO NOT use with incompatible components or in any way otherwise as mentioned or instructed in the product documents provided by ZHIYUN. The safety guidelines herein contain instructions for safety, operation and maintenance. It is essential to read and follow all of the instructions and warnings in the User Guide, prior to assembly, setup or use, in order to operate the product correctly and avoid damage or serious injury.

Safe Operation Guidelines

1. This product is a high-precision control device. Damage may be caused to this product if dropped or subject to external force, and this may result in malfunction.
2. Make sure the rotation of the gimbal axes is not blocked by external force when this product is turned on.
3. this product is not waterproof. Prevent contacts of any kind of liquid or cleaner with the this product. It is recommended to use dry cloth for cleaning.
4. Protect this product from dust and sand during use.

Warranty Period

1. Customers are entitled to replacement or free repair service in case of quality deficits found in the product within 15 days upon receipt of the product.
2. Customers are entitled to free repair service from ZHIYUN for any product proven defective in material or workmanship that results in product failure during normal consumer usage and conditions within the valid warranty period, which is 12 months counting from the date of selling. However, warranty period varies by product component and country of purchase. Please contact our after-sales service team on ZHIYUN official website or your place of purchase for detailed warranty information.

Warranty Exclusions

1. Products subjected to unauthorized repair, misuse, collision, neglect, mishandling, soaking, accident, and unauthorized alteration.
2. Products subjected to improper use or whose labels or security tags have been torn off or altered.
3. Products whose warranty has expired.
4. Products damaged due to force majeure, such as fire, flood, lightning, etc.

Warranty Claim Procedure

1. If failure or any problem occurs to your product after purchase, please contact a local agent for assistance, or you can always contact ZHIYUN's customer service through email at info@zhiyun-tech.com or website at www.zhiyun-tech.com.
2. Your local agent or ZHIYUN's customer service will guide you through the whole service procedure regarding any product issue or problem you have encountered. ZHIYUN reserves the right to reexamine damaged or returned products.

Customer Information

Customer Name:

Phone Number:

Address:

Sales Information

Sales date:

Product Serial Number:

Distributor Name:

Distributor's Contact Number:

First Maintenance Record

Service Date:

Repairman Signature:

Cause of Problem:

Service Result:

Solved

Unsolved

Refunded/Replaced



Website



Weibo



Vimeo



Google+



Facebook
(Zhiyun Support)



Facebook
(Zhiyun Tech)



Youku



Youtube



Wechat



Instagram

Tel: +86 400 900 6868

USA Hotline: +1 808-319-6137,9:00-18:00 GMT-7,Mon-Fri

Europe Hotline: +49 (0) 61018132180,10:00-17:00 GMT+1,Mon-Fri

Web: www.zhiyun-tech.com

E-mail: info@zhiyun-tech.com

Address: 09 Huangtong Road, Tieshan Industrial Zone, Qixing District, Guilin, 541004, Guangxi, China

Certificate of Quality

This product is confirmed to meet quality standards and permitted for sale after strict inspection.

QC Inspector: _____



For full product information, please visit ZHIYUN's official website: Content on www.zhiyun-tech.com is subject to update without notice.

ZHIYUN™ is a trademark of ZHISHEN

All product names or brands referred to hereunder may be trademarks or registered trademarks of their respective holders.

Copyright © 2024 ZHISHEN. All rights reserved.

ZHIYUN-TECH.COM