



Kali600 Studio LED



COLOR RENDERING INDEX
CRI 95+



TEMPERATURE CONTROL



POWER CONTROL



BATTERY POWERED



AC POWER

The Phottix Kali Series - Phottix line-up of LED panels for video or still photography. For use on-location or in the studio

Features:


- Excellent color rendering - CRI 95+
- Digital Power Control: 10% - 100%
- Digital Color Control: 3300K - 5600K
- Uses 2 Sony-compatible batteries or AC Adapter



Removable Barndoors



Removable White Diffuser Panel



Honeycomb and Gel Set Kit (sold separately)

The Phottix Kali600 features a maximum brightness of 3000Lux (36W). Being both mains and battery powered it can be used in the studio or on-location. The Kali600 offers power and color temperature control – on-board, and via a wireless radio remote. Barndoors, white diffuser panel and AC Adapter are included.



Kali600 Studio LED Technical Specs:

SKUs / Model:	Phottix Kali600 Studio LED
Color Rendering Index (CRI):	≥ 95
Color Temperature (adjustable):	3300K~5600K
Maximum Brightness:	3000Lux @ 1m
Power:	36W @ full power
Battery:	2 x Compatible NP Series (NP-F550 / 750 / 960)
Battery Life:	2 x NP-F550 (7.4V 2000mAh) 90min
5600K at Max Power	2 x NP-F750 (7.4V 4600mAh) 240min
	2 x NP-F970 (7.4V 6600mAh) 3600min
Remote Control Range:	>50m
Dimensions:	242mm x 191mm x 42mm (9.5" x 7.5" x 1.7")
Weight:	1340g (not include battery / barndoor)

81440 Phottix Kali600 Studio LED

20900 Phottix Kali600 Honeycomb and Gel Set Kit