



JUNO Li60

Transceiver Flash

Powered by Odin Z

Light all day and night



- 
Odin Z OS
- 
ARES II Receiver
- 
HSS SUPPORT
- 
LITHIUM BATTERY
- 
REMOTE POWER-CONTROL

The new Juno Li60 Flash packs Professional power and super-fast recycle times in a manual flash.

With a 3200mAh Li-ion battery, the Phottix Juno Li60 with serious power for serious professionals, super-charged with Phottix's new Odin Z Operating System.

Features:

- Long-lasting Lithium-Ion Battery
- Fast recycle times
- Pair with Phottix Odin Lite for the ultimate in manual control on any camera system
- Real time manual power display
- Compatible with other Phottix Ecosystem products*

* Built-in power control with Phottix Odin II or Odin Lite, triggering only with Phottix Ares II or Strato II Triggers

SKU: 80310 Phottix Juno Li60 Transceiver Flash

When paired with the Phottix Odin Lite controller, the Juno Li60 can be controlled and triggered from any camera system. Perfect for photographers shooting with different camera bodies, trigger with Odin II for HSS.

This Odin Lite and Li60 combo is the perfect travel companion for photographers on the road. Shoot all day and night and never worry about missing a shot. Power, Speed and Control – the busy location photographers new workhorse.

Juno Li60 Transceiver Flash Technical Specs:

Guide No:	GN60 at 200mm zoom
Wireless range:	not less than 100m
Wireless Mode:	OdinII TX, OdinII RX, AresII RX, S1/S2 RX
Battery power:	Li-ion battery 7.4V 3200mAh
Battery life:	Up to 800 cycles @ full power
Recycling time:	Up to 1.5 Seconds @ full power
Rotation:	180 degree left and right ; Up, Down: -7 to 90 degree
Dimensions:	79 x 60 x 193mm
Weight:	410g (not include battery)

Pre-production specifications.