

CRANE 4 Camera Compatibility List



Update on June 13, 2023 (Firmware version V1.76)

V1.00

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	1DX Mark III、 1DX Mark II、 5DS、 5DS R、 5D Mark III、 5D Mark IV、 6D Mark II、 6D、 90D、 80D、 850D、 800D、 200D II	EF 8-15mm f/4L USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 11-24mm f/4L USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
	EF 16-35mm f/4L IS USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	1DX Mark III、 1DX Mark II、 5DS、 5DS R、 5D Mark III、 5D Mark IV、 6D Mark II、 6D、 90D、 80D、 850D、 800D、 200D II	EF 16-35mm f/2.8L III USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 17-40mm f/4L USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24-70mm f/2.8L II USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	1DX Mark III、 1DX Mark II、 5DS、 5DS R、 5D Mark III、 5D Mark IV、 6D Mark II、 6D、 90D、 80D、 850D、 800D、 200D II	EF 24-70mm f/4L IS USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24-105mm f/4L IS II USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24mm f/1.4L II USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	1DX Mark III、 1DX Mark II、 5DS、 5DS R、 5D Mark III、 5D Mark IV、 6D Mark II、 6D、 90D、 80D、 850D、 800D、 200D II	EF 35mm f/1.4L II USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 50mm f/1.2 USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 50mm f/1.4 USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 50mm f/1.8 USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 85mm f/1.2L IS USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	1DX Mark III、 1DX Mark II、 5DS、 5DS R、 5D Mark III、 5D Mark IV、 6D Mark II、 6D、 90D、 80D、 850D、 800D、 200D II	EF 85mm f/1.4L IS USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 85mm f/1.8 USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS R, R5, R6, R5C, R7, R8, R50, R10, RP, C70, R6 Mark II (use mount adapter EF-RF for non-RF lenses)	Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		RF 24-70mm f/2.8 L IS USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS R, R5, R6, R5C, R7, R8, R50, R10, RP, C70, R6 Mark II (use mount adapter EF-RF for non-RF lenses)	RF 24-70mm f/2.8 L IS USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		RF24-105mm F4 L IS USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		RF28-70mm F2 L	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS R, R5, R6, R5C, R7, R8, R50, R10, RP, C70, R6 Mark II (use mount adapter EF-RF for non-RF lenses)	RF35mm F1.8	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		RF50mm F1.2 L USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		RF85mm F1.2 L USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	D850、 D780、 D810、 D750、 D610、 D7500、 D6	AF-S NIKKOR 14-24mm f/2.8G ED	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 16-35mm f/4G ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S Zoom-NIKKOR 17-35mm f/2.8D IF-ED	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	D850、 D780、 D810、 D750、 D610、 D7500、 D6	AF-S NIKKOR 18-35mm f/3.5-4.5G ED	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 24-70mm f/2.8E ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 24-70mm f/2.8G ED	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	D850、 D780、 D810、 D750、 D610、 D7500、 D6	AF Zoom-NIKKOR 24-85mm f/2.8-4D IF	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 24-85mm f/3.5-4.5G ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
	AF-S NIKKOR 24-120mm f/4G ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	D850、 D780、 D810、 D750、 D610、 D7500、 D6	AF-S NIKKOR 28-300mm f/3.5-5.6G ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF NIKKOR 14mm f/2.8D ED	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 20mm f/1.8G ED	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 24mm f/1.4G ED	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 24mm f/1.8G ED	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	D850、 D780、 D810、 D750、 D610、 D7500、 D6	AF-S NIKKOR 35mm f/1.4G	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 50mm f/1.4G	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 85mm f/1.4G	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 85mm f/1.8G	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 24-70mm f/2.8L DG	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark	
				Horizontal	Vertical	Horizontal	Vertical			
Nikon	D850、 D780、 D810、 D750、 D610、 D7500、 D6	Sigma 35mm F1.4 DG	Camera and lens	√	√	-	-		No need to remove eyepiece cap	
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap	
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap	
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap	
		Sigma 50mm F1.4 DG	Camera and lens	√	√	-	-		No need to remove eyepiece cap	
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap	
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap	
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap	
		Z9、 Z8、 Z fc、 Z50、 Z5、 Z6、 Z6 II、 Z7、 Z7 II、 Z30、 Z50	NIKKOR Z 24-70mm f/2.8S	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
				with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
				with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
				with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
				with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
				with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			NIKKOR Z 24-70mm f/4S	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
				with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
				with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
				with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
with transmission transmitter and zoom/focus motor (for focus control)	√			√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap		
with transmission transmitter and zoom/focus motor (for zoom control)	√			√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z9、Z8、Z fc、Z50、Z5、Z6、Z6 II、Z7、Z7 II、Z30、Z50	NIKKOR Z 35mm f/1.8S	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		NIKKOR Z 50mm f/1.8S	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 14-24mm f/2.8G ED	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 16-35mm f/4G ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z9, Z8, Z fc, Z50, Z5, Z6, Z6 II, Z7, Z7 II, Z30, Z50	AF-S Zoom-NIKKOR 17-35mm f/2.8D IF-ED	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 18-35mm f/3.5-4.5G ED	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 24-70mm f/2.8E ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z9、Z8、Z fc、Z50、Z5、Z6、Z6 II、Z7、Z7 II、Z30、Z50	AF-S NIKKOR 24-70mm f/2.8G ED	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF Zoom-NIKKOR 24-85mm f/2.8-4D IF	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 24-85mm f/3.5-4.5G ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z9、 Z8、 Z fc、 Z50、 Z5、 Z6、 Z6 II、 Z7、 Z7 II、 Z30、 Z50	AF-S NIKKOR 24-120mm f/4G ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 28-300mm f/3.5-5.6G ED VR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		AF NIKKOR 14mm f/2.8D ED	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 20mm f/1.8G ED	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z9, Z8, Z fc, Z50, Z5, Z6, Z6 II, Z7, Z7 II, Z30, Z50	AF-S NIKKOR 24mm f/1.4G ED	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 24mm f/1.8G ED	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 35mm f/1.4G	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 50mm f/1.4G	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		AF-S NIKKOR 85mm f/1.4G	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z9、Z8、Z fc、Z50、Z5、Z6 II、Z7、Z7 II、Z30、Z50	AF-S NIKKOR 85mm f/1.8G	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 24-70mm f/2.8L DG	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Sigma 35mm F1.4 DG HSM Art	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 50mm F1.4 DG	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α9M2、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX6	FE 16-35mm F2.8 GM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		FE 16-35mm F4 ZAISS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		FE 12-24mm F4 G	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		FE 24mm f1.4GM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α9M2、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX6	FE 24-70mm F2.8 GM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		FE 24-70mm F4 ZA OSS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		FE 28mm F2	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		FE 50mm F1.8	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		FE 85mm F1.4 GM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α9M2、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX6	Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sonnar® T* FE 50mm F1.8 ZA	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		E 10-18mm F4 OSS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α9M2、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX6	E 16-70mm F4 OSS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		E PZ 18-105mm F4 G OSS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		FE 24-105mm f/4 G OSS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
	E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α9M2、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX6	Sigma 16mm f/1.4 DC DN	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 24mm f1.4 DG	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 50mm f/1.4 DG	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α9M2、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX6	Sigma 56mm F1.4 DC DN	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Tamron 28-75mm f/2.8	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		sigma18-35mm f/1.8 DC HSM Art (+Canon adapter ring)	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
	with zoom/focus motor (for zoom control)		√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
	with transmission transmitter		√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
	with transmission transmitter and zoom/focus motor (for focus control)		√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
	with transmission transmitter and zoom/focus motor (for zoom control)		√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
FUJIFILM	X-H1, X-T2, X-T3, X-T4, X-T5, X-H2s	XF 10-24mm f/4.0 R OIS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		XF 16-55mm f/2.8 R LM WR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
	XF 18-55mm f/2.8-4 R OIS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
FUJIFILM	X-H1、 X-T2、 X-T3、 X-T4、 X-T5、 X-H2s	XF 16-80mm f1.4 R OIS WR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		XF 35mm f/2 R WR	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		XF 56mm f/1.2 R	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
FUJIFILM	X-H1, X-T2, X-T3, X-T4, X-T5, X-H2s	XC 15-45mm f/3.5-5.6 OIS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		XC 16-50mm f/3.5-5.6 OIS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
	Super EBC XF 23mm f/1.4 R	Camera and lens	√	√	-	-		No need to remove eyepiece cap	
		with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap	
		with transmission transmitter	√	-	-	-		No need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap	



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Panasonic	G9, GH5s, GH5, GH6, DC-BGH1	Vario-Elmarit 8-18mm f/2.8-4.0	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Vario 12-35mm f/2.8 II	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Vario-Elmarit 12-60mm f/2.8-4	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Panasonic	G9, GH5s, GH5, GH6, DC-BGH1	SUMMILUX 12mm f/1.4	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Lumix G 25mm f/1.7	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		SUMMILUX 15mm f/1.7	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		MACRO 30mm f/2.8	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		M.ZUIKO DIGITAL ED 12-40mm f/2.8 PRO	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Panasonic	G9, GH5s, GH5, GH6, DC-BGH1	M.ZUIKO DIGITAL ED 7-14mm f/2.8 PRO	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		M.Zuiko Digital ED 12-100mm f/4.0 IS PRO	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
	sigma 18-35mm f/1.8 DC HSM Art (+adapter ring)	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Panasonic	S5, S1, S1H	LUMIX S 24-105mm F/4 Macro OIS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		LUMIX S 24-70mm F/4 Macro OIS	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMCC 4K	Vario-Elmarit 8-18mm f/2.8-4.0	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Vario 12-35mm f/2.8 II	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Vario-Elmarit 12-60mm f/2.8-4	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		SUMMILUX 12mm f/1.4	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMPC4 4K	25mm f/1.7	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		SUMMILUX 15mm f/1.7	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		MACRO 30mm f/2.8	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		M.ZUIKO DIGITAL ED 12-40mm f/2.8 PRO	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BM PCC 4K	M.ZUIKO DIGITAL ED 7-14mm f/2.8 PRO	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		M.Zuiko Digital ED 12-100mm f/4.0 IS PRO	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Sigma18-35mm f/1.8 DC HSM Art (+adapter ring)	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMPCC 6K, BMPCC 6K PRO	EF 8-15mm f/4L USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 11-24mm f/4L USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 16-35mm f/4L IS USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMPCC 6K, BMPCC 6K PRO	EF 16-35mm f/2.8L III USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 17-40mm f/4L USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24-70mm f/2.8L II USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMPCC 6K, BMPCC 6K PRO	EF 24-70mm f/4L IS USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24-105mm f/4L IS II USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24mm f/1.4L II USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-		No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMPCC 6K, BMPCC 6K PRO	EF 35mm f/1.4L II USM	Camera and lens	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 50mm f/1.2L USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 50mm f/1.4L USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 50mm f/1.8 STM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 85mm f/1.2L II USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMPCC 6K, BMPCC 6K PRO	EF 85mm f/1.4L IS USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 85mm f/1.8 USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 18-35 T2 (EF)	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
	with transmission transmitter and zoom/focus motor (for focus control)		√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	
	with transmission transmitter and zoom/focus motor (for zoom control)		√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sigma	fp	45mm F2.8	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
ZCAM	E2, E2C	Panasonic Lumix G Vario 7-14mm f/4 ASPH	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Panasonic Leica DG Vario-Elmarit 8-18mm f/2.8-4 ASPH.	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
ZCAM	E2, E2C	Panasonic Lumix GX Vario 12-35mm f/4 ASPH	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Panasonic Lumix 14mm f/2.5 G	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Lumix G X Vario 14-42mm f/3.5-5.6 Power O.I.S	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Panasonic Lumix G Vario 14-140mm f/3.5-5.6 ASPH. POWER O.I.S	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
ZCAM	E2, E2C	Panasonic Leica DG Summilux 15mm f/1.7 ASPH.	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Panasonic Lumix G 25mm f/1.7 ASPH	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Panasonic Lumix G 42.5mm f/1.7 ASPH	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Panasonic Leica DG Macro-Elmarit 45mm f/1.7 ASPH.	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 19mm F2.8 DM Art	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
ZCAM	E2, E2C	Olympus M.Zuiko Digital ED 7-14mm f/2.8 PRO	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Olympus M.Zuiko Digital ED 8mm f/1.8 Fisheye PRO	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Olympus M.Zuiko Digital ED 12mm f/2	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Olympus M.Zuiko Digital ED 12-40mm f/2.8 PRO	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
ZCAM	E2, E2C	Olympus M.Zuiko Digital ED 12-100mm f/2.8 IS PRO	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		Olympus M.Zuiko Digital ED 14-42mm f/3.5-5.6 EZ	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
	Olympus M.Zuiko Digital ED 17mm f/1.2 PRO	Camera and lens	√	√	-	-		No need to remove eyepiece cap	
		with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap	
		with transmission transmitter	√	-	-	-		No need to remove eyepiece cap	
		with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
ZCAM	E2 F6	Olympus M.Zuiko Digital ED 25mm f/1.2 PRO	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Olympus M.Zuiko Digital ED 30mm f/3.5 Macro	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Olympus M.Zuiko Digital ED 45mm f/1.2 PRO	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Olympus M.Zuiko Digital ED 60mm f/2.8 Macro	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Olympus M.Zuiko Digital ED 75mm f/1.8 Lens	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
ZCAM	E2 F6	EF 8-15mm f/4L USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 11-24mm f/4L USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 16-35mm f/4L IS USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
ZCAM	E2 F6	EF 17-40mm f/4L USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24-70mm f/4L IS USM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	√	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	-	-	Zoom/focus motor installed on either side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 24mm f/1.4L II USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
ZCAM	E2 F6	EF 35mm f/1.4L II USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 50mm f/1.2L USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 50mm f/1.4 USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 50mm f/1.8 STM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		EF 85mm f/1.2L II USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
EF 85mm f/1.4L IS USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap		
	with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap		
	with transmission transmitter	√	-	-	-		No need to remove eyepiece cap		
	with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
ZCAM	E2 F6	EF 85mm f/1.8 USM	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	√	-	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap
			with transmission transmitter	√	-	-	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	√	-	-	Zoom/focus motor installed on either side	No need to remove eyepiece cap