

ZHIYUN

ZHIYUN-TECH.COM



# MOLUS B SERIES COB LIGHT

MOLUS (B100) | MOLUS (B200) | MOLUS (B300) | MOLUS (B500)



DynaVort  
Cooling System™



Power Source  
Lighting Integration



Bluetooth Mesh

2700K  
6500K

CCT Range



Scan for more info





## Power Source + Lighting Integration

The B series integrated the light with the power source to liberates you from the shackles of external power and tangled wires even in lights with 500W high power. With just a single AC cable, you'll ignite your creative spark and conquer the realm of photography with unparalleled ease and style.

## Intuitive Dials and Control

Effortlessly conjure the perfect ambiance with the intuitive control dials, granting you unparalleled precision over brightness and color temperature. Switch between presets or fine-tune your settings with the external dimmer, empowering you to adapt to any lighting scenario with ease.



## 2700K-6500K for Pro Color Rendering

Capture the perfect shot in any light with B Series' mastery. Glide seamlessly through 2700K to 6500K, the lights render colors with cinematic flair, no matter in bold scenes or subtle hues.

## Compatible with Bowens Mount

Craft the perfect light with ZHIYUN's precision accessories. From sleek modifiers to universal Bowens mount compatibility—mix, match, and master any illumination challenge.

| PRODUCT SPECS  | MOLUS (B100)    | MOLUS (B200)    | MOLUS (B300)    | MOLUS (B500)    |
|--|-----------------|-----------------|-----------------|-----------------|
| Light Net Weight (with bracket)                                  | 1.27kg          | 1.40kg          | 2.57kg          | 2.80kg          |
| Light Size (with bracket)  | 146*181*160mm   | 146*181*160mm   | 245*190*159mm   | 245*190*159mm   |
| CRI  | ≥96             | ≥96             | ≥95             | ≥95             |
| TLCI   | ≥96             | ≥96             | ≥97             | ≥97             |
| CCT Range  | 2700K-6500K     | 2700K-6500K     | 2700K-6500K     | 2700K-6500K     |
| TM-30 Rf   | 94(on average)  | 94(on average)  | 94(on average)  | 94(on average)  |
| TM-30 Rg   | 101(on average) | 101(on average) | 101(on average) | 101(on average) |
| Illuminance (lux)<br>(without reflector, 5500K, 1m)              | 4160            | 8370            | 12400           | 19200           |
| Illuminance (lux)<br>(with ZHIYUN standard reflector, 5500K, 1m) | 20600           | 39900           | 63200           | 76400           |

\*Data collected from internal experiments of ZHIYUN laboratories. Please refer to the actual product.